# CRATYA

WALL LIGHT · THE HARMONY OF OUTDOOR CURVES



## THE PIECE

Soften the architecture of your facade with the elegant curved lines of the CRATYA wall light. Breaking away from traditional harsh lines, this model features a rounded silhouette where a large opal diffuser appears supported by a sleek base made of solid aluminum alloy .

## MATERIALS

Curved Acrylic Block
CRI > 80


## SERVICES

| | |
|---|---|
| 30-day returns | From delivery |
| Ships in 1–2 days | Tracked delivery |
| IP65 | Weather Protection |
| 3000K | Color Temperature |

# Specifications

| | |
|---|---|
| Architectural Shield | Thickened Aluminum Alloy (Anti-Corrosion Black Finish) |
| Weather Protection | IP65 (Completely Waterproof and Dustproof) |
| Diffuser | Curved Acrylic Block (Soft, Panoramic Light) |
| LED Technology | Integrated 18W LED Module (High Performance) |
| Color Rendering | CRI > 80 (Perfectly Preserves Facade Hues) |
| Color Temperature | Choice of: Warm White (3000K), Natural, or Cool White |
| Dimmable | Non-Dimmable (Standard Wall Switch) |
| Voltage & Safety | AC 110V-220V (CE Certified) |

# Dimensions




| | |
|---|---|
| Standard Dimensions | H 26 cm x W 14 cm x D 10 cm |
| Environment | Outdoor-Specific (100% Waterproof) |
| Installation | Wall-Mounted (Fixed Electrical Wiring) |

Hallway or living room
Centre the light about 150–170 cm above the floor; in a row, space them 80–120 cm apart.

Bedside
As a pair, about 120–140 cm above the floor, one on each side of the bed.

Around a mirror
At eye level, about 160–170 cm above the floor, one on each side.

# Finishes



**Warm white (3000K)**

# Installation & care

Must be installed by a qualified electrician, in line with local wiring regulations (BS 7671 in the UK).

Switch off at the mains before fitting or cleaning.

Integrated LED: no bulb to change.

Fabric shade: soft brush or gentle vacuum.